

School of Civil Engineering

FACULTY OF ENGINEERING



UNIVERSITY OF LEEDS

# Using piled foundations as ground heat exchangers

Dr Fleur Loveridge

Royal Academy of Engineering Research Fellow

University Academic Fellow

[F.A.Loveridge@leeds.ac.uk](mailto:F.A.Loveridge@leeds.ac.uk)

13<sup>th</sup> October 2016

# Acknowledgements



UNIVERSITY OF LEEDS

Royal Academy of Engineering (UK); (with support from Mott MacDonald, Arup, Cementation Skanska, WJ Groundwater, GI Energy, Neo-Energy, Mimer Energy, British Geological Survey)

Engineering & Physical Sciences Research Council (UK); (with support from Mott MacDonald, Cementation Skanska, Golder Associations & W J Groundwater)

Professor William Powrie & University of Southampton

Siemens Plc, Arup, BBGE, FDL Ltd, IGS

Maria Alberdi, Aalborg University & Centrum Paele A/S  
(Denmark)

Cementation Skanska (UK)

# Using piled foundations as ground heat exchangers



UNIVERSITY OF LEEDS

- What is an energy pile?
- Construction of energy piles
- Design of energy piles
- Thermal response testing
- Case studies
  - The Crystal building (London, UK)
  - Rosborg Gymnasium (Vejle, Denmark)



# What is an energy pile?

- A pile is a relatively long and slender structural member used to transmit foundation loads to the ground
  - End bearing piles
  - Friction piles
  - Laterally loaded piles
- Contain steel reinforcement to carry bending moments and shear forces
- Can be equipped with heat transfer pipes for integration into GSHP system




# Types of pile construction



UNIVERSITY OF LEEDS

Depends on geology and site access:

- Rotary bored
- Continuous flight auger (CFA)
- Driven piles
  - Steel – H section; hollow cylinder
  - Precast concrete
- Screw piles



Above images courtesy of Cementation Skanska



# Types of pile construction

Depends on geology and site access:

- Rotary bored
- Continuous flight auger (CFA)
- Driven piles
  - Steel – H section; hollow cylinder
  - Precast concrete
- Screw piles



# Types of pile construction



UNIVERSITY OF LEEDS

Depends on geology and site access:

- Rotary bored
- Continuous flight auger (CFA)
- Driven piles
  - Steel – H section; hollow cylinder
  - Precast concrete
- Screw piles



Image courtesy of Geologic Foundations



Images courtesy of Maria Alberdi



# Construction challenges I


- Pre-fabrication vs on site installation of loops
- Prevention of damage:
  - Concreting >> use of tremmie
  - Pile break out
  - Protection by foam
  - Groundworks
- Pressure testing at handover





# Construction challenges II

- Coordination and contractual arrangements
- Construction Interfaces:
  - Piling
  - Groundworks
  - M & E
  - Control systems
- Redundancy (design vs construction)



# How much energy is obtainable?



UNIVERSITY OF LEEDS

- Rules of thumb: 20 – 75 W/m (CIBSE, 2013)
- Borehole rules of thumb: 20 – 55 W/m (CIBSE, 2013)

Reference	Pile Type	Pile Dia (mm)	Monitoring Period	COP / SPF*	Heat Transfer Rate (W/m)
Henderson et al., 1998	Steel tubes with concrete infill	200	12 months		16.4 extraction 18.3 injection
Wood et al., 2010a, b	Bored cast in situ	300	7 months		26
Murphy et al., 2015	Bored cast in situ	910	22 months		91, 95
Pahud & Hubbach, 2007	Bored cast in situ	900 - 1500	24 months	2.7 to 3.9 (SPF)	15 extraction 16 rejection
Sekine et al., 2007	Bored cast in situ	1500	15 months	3.2 extraction (COP) 3.7 injection (COP)	120 extraction 100 – 220 rejection
Kipry et al., 2009	Various schemes			3 to 6.5 (SPF)	<30 extraction <35 injection



Differences to classical borehole schemes:

- Length constrained by structural design
- Plan arrangements likely to be irregular
  - Several closely spaced piles under structural columns
  - Wider spacing in between
- Much shorter aspect ratio
  - Larger diameter (short term issues)
  - Shorter length (long term issues)

# Design considerations: short term







UNIVERSITY OF LEEDS

a) 300mm driven

b) 450mm driven

c) 300mm or 1200mm rotary bored


d) 300mm or 1200mm bored CFA





# Example temperature changes


- Temperature difference between pipes and pile edge as measure of thermal behaviour
- For given 20 W/m constant heat input at  $\lambda_c = \lambda_g = 2 \text{ W/mK}$
- Smaller pile >>
  - bigger temperature difference (fewer pipes)
  - Temperature difference appears to stabilise sooner
- Convert to thermal resistance



# Pile thermal resistance (circular cross section, rotary bored)




UNIVERSITY OF LEEDS



# Time for pile to reach steady state



UNIVERSITY OF LEEDS




# Transient approach to resistance



UNIVERSITY OF LEEDS

- It may take several days for a pile to reach steady state
- Operational conditions are rarely steady
- Must have transient short time step analysis
  - Combined pile and concrete G-function (no pile resistance term)
  - Transient function for pile resistance




# Analytical Example



UNIVERSITY OF LEEDS

- 600mm dia pile, 20m long
- Hourly time steps
- Analytical temperature response functions (G-functions)
- Potentially 20% underestimate of energy for steady analysis






- Important to agree temperature limits with geotechnical & heat pump design teams
- Piles have short aspect ratio (AR) – making boundary conditions more important
- Classic borehole design assumes constant surface temperature >> Low AR >> reach steady state sooner
- Analysis has shown that for short heat exchangers this underestimates the benefit of surface thermal recharge
- But for piles beneath a building an insulated or net heat flux boundary condition may be more appropriate

# Design considerations: long term





UNIVERSITY OF LEEDS



Bidarmaghz et al 2016:

- 4 no 30m deep ground heat exchangers
- Surface thermal recharge can cause reduced ground temperature change
- Effect 40% bigger compared to 50m deep installations







# Design considerations: long term

Monitoring data from active systems beneath buildings:

- Mikhaylova et al (2016) & Habert et al (2016) show some fluctuations at the pile head.



Above: Mikhaylova et al (2016) Ground thermal response to borehole ground heat exchangers, Proc ICEG

Left: Habert et al (2016) Lessons learnt from mechanical monitoring of thermoactive pile, Proc ICEG



# Thermal response testing for piles

## Size restrictions for TRT

- IGSHPA >> 152 mm
- GSHPA >> 200 mm

$$\Delta T = qR_b + \frac{q}{4\pi\lambda} \left\{ \ln \left( \frac{4\alpha t}{r^2} \right) - \gamma \right\}$$

## Why?

- Exponential Integral in line source model
- Heat capacity of grout / concrete

$$\Delta T = qR_b + \frac{q}{4\pi\lambda} \left\{ Ei \left( \frac{r^2}{4\alpha t} \right) \right\}$$

For piles larger  $r$  >> larger minimum time



$$Fo = \frac{4\alpha t}{r^2}$$

$$Fo > 5$$

# Quantification of Model Errors



UNIVERSITY OF LEEDS




# Axial Effects in TRT ?



UNIVERSITY OF LEEDS


Typical TRT time range



# Field to lab thermal conductivity for energy piles



UNIVERSITY OF LEEDS





- If you must do a pile TRT:
  - Give due regard to diameter when determining test length
  - Don't just use the line source to interpret the results; use a transient model or numerical simulation (ideally 3D) with parameter estimation
  - Remember it likely has reduced accuracy
- Consider testing a borehole at site investigation stage:
  - More accurate; easier to interpret
  - Fewer programme issues (heat of hydration, critical path)
  - Pile length may not yet be known (less issue for end bearing driven?)
  - No concrete resistance / thermal properties information

# Case study: The Crystal



UNIVERSITY OF LEEDS

- Siemens landmark new building in East London
- All electric building
- 160 energy piles (600mm to 1200mm diameter; 21m deep)
- 36 closed loop boreholes (137.5 mm diameter; 150m deep) into the Chalk



# Construction



UNIVERSITY OF LEEDS



# Construction




UNIVERSITY OF LEEDS



# Geology


- Piles
  - Made ground, alluvium, river gravels & London Clay
- Boreholes
  - Full London basin sequence, including Thanet Sands and Chalk aquifer
- High groundwater table



# Heat pump arrangement



UNIVERSITY OF LEEDS



heating and cooling delivery in the Crystal

# Thermal Demand




UNIVERSITY OF LEEDS



Predicted demand: Heating 307 MWh/yr; Cooling 173 MWh/yr

Actual usage: Heating ~ 550 MWh/yr; Cooling ~ 550 MWh/yr

Nominal 600kW systems: actual 399 kW H & 572 kW C




# Pile monitoring



# Pile behaviour




UNIVERSITY OF LEEDS



# Apparent thermal resistance




UNIVERSITY OF LEEDS



# Heat transferred to the ground




UNIVERSITY OF LEEDS



# Seasonal Performance Factor



UNIVERSITY OF LEEDS



# Case study: Rosborg Gymnasium



UNIVERSITY OF LEEDS


- 2011 extension founded on 200 energy piles
- 2 story building
- 0.3m square 15m long driven precast concrete piles
- Each with “W” pipe loop
- 16 piles grouped in series
- Glacial sediments; high natural groundwater is artificially drained



# Construction



UNIVERSITY OF LEEDS




# Heat pump arrangement




UNIVERSITY OF LEEDS


°C Outside ambient temperature




Energy piles

Sensor position. Reference level: surface (positive cote downwards).









- Piles can potentially offer cost & carbon savings compared to boreholes; may be more efficient per linear metre.
  - But still require same care and attention in terms of system design
- Need to consider thermal storage in pile for design & TRT.
- Need to consider short length and potential for revised boundary condition in long term.
- Must liaise with geotechnical designers about temperature changes/limits.
- Must consider construction interfaces and damage avoidance; site coordination essential